

Technical sheet :

# **MH 25**

---



 **MANITOU**  
HANDLING YOUR WORLD

Technical characteristics			Metric
1.1	Manufacturer		Manitou
1.2	Model Name		MH 25
1.3	Power source		Diesel
1.4	Operator type		Seated
1.5	Max. capacity	Q	2500 kg
1.6	Load center of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	625 mm
1.9	Wheelbase	y	1800 mm
Weight			
2.1	Service weight		4260 kg
2.2	Weight on front axle (laden) / rear axle (laden)		5812 kg / 948 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1750 kg / 2510 kg
Wheels			
3.1	Tires type		Inflatable
3.2	Dimensions of front wheels		280/80 R20 XMCL
3.3	Dimensions of rear wheels		27,10 - 12 IC 30 14PR
3.5	Number of front wheels / rear wheels		2 / 2
3.5.2	Number of drive wheels		4
3.6	Front wheel gauge	b10	1160 mm
3.7	Rear wheel gauge	b11	1164 mm
Dimensions			
4.7	Height of overhead guard (cabin)	h6	2105 mm
4.8	Seat height/stand height	h7	1025 mm
4.19	Overall length	l1	4045 mm
4.20	Length to face of forks	l2	2945 mm
4.21	Overall width	b1	1450 mm
4.22	Forks section x width x length	s / e / l	40 mm x 100 mm / 1100 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		2A
4.24	Fork carriage width	b3	1260 mm
4.31	Ground clearance below mast	m1	260 mm
4.32	Ground clearance at centre of wheelbase	m2	260 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	5290 mm
4.35	Turning radius	Wa	3265 mm
Performances			
5.1	Travel speed (laden / unladen)		14 km/h / 14 km/h
5.2	Lifting speed (laden / unladen)		0.40 m/s / 0.50 m/s
5.3	Lowering speed (laden / unladen)		0.50 m/s / 0.40 m/s
5.5	Drawbar pull (Laden)		3550 daN
5.7	Gradeability (laden / unladen)		50 % / 48 %
5.10	Service brake		Hydraulic
Engine			
7.1	Engine brand / model / nom		Kubota / V2403 M-E3B / Stage IIIA
7.2	Engine power (Hp / kW)		49 Hp/36 kW
7.3	Rated speed		2700 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 2434 cm³
Miscellaneous			
8.2	Working hydraulic pressure for attachments		170 bar
8.3	Oil flow rate for attachments		77 l/min

## Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 27	FVD 30	FVD 33	FVD 35	FVD 37	FVD 40	FVD 45	FVD 50	FVD 55	FVD 60
α - Mast/fork carriage tilt, forward	°	10	10	10	10	10	10	10	6	6	6
β - Mast/fork carriage tilt, backward	°	12	12	12	12	12	12	12	6	6	6
h1 - Mast lowered height	mm	1995	2145	2295	2395	2555	2745	2995	3245	3495	3785
h2 - Mast free lift	mm	130	130	130	130	130	130	130	130	130	130
h4 - Mast extended height	mm	3531	3831	4070	4331	4531	4831	5331	5831	6331	6831
Residual capacity at max height	kg	2500	2500	2500	1900	1900	1550	1100			
Height at max capacity	mm	2500	2500	2500	2500	2500	2500	2500	2500	2500	2500

Free Lift Triplex (FLT)		FLT 37	FLT 40	FLT 43	FLT 47	FLT 50	FLT 55	FLT 60	FLT 65	FLT 70
α - Mast/fork carriage tilt, forward	°	10	10	10	10	6	6	6	6	6
β - Mast/fork carriage tilt, backward	°	12	12	12	12	6	6	6	6	6
h1 - Mast lowered height	mm	1945	2045	2145	2295	2395	2555	2745	2995	3245
h2 - Mast free lift	mm	1221	1321	1421	1571	1671	1831	2021	2271	2521
h4 - Mast extended height	mm	4469	4769	5069	5469	5769	6269	6769	7269	7769
Residual capacity at max height	kg	1900	1550	1250	1000		700			
Height at max capacity	mm	2500	2500	2500	2500	2500	2500	2500	2500	2500
Height at max capacity with integrated sideshift	mm				4300					



 **MANITOU**  
**HANDLING YOUR WORLD**

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes